



CLEAR[™]
NANOBUBBLE GENERATOR



APPLICATIONS

- Pond & Lake Treatment
- Horticulture & Irrigation Reservoir Treatment
- Algae Control
- Water Quality Improvement
- Odor Control
- Iron & Manganese Control
- Midge Fly Control
- Hypolimnetic Aeration
- Sediment Decomposition
- Fish and Ecosystem Health
- Side Stream Oxygenation
- Nutrient Reduction

Moleaer's patented Clear[™] nanobubble generator is a chemical-free solution for improving water quality and restoring the natural health of lakes and ponds. The Clear is a hyper-efficient gas-injection technology that uses air to produce a constant, concentrated stream of nanobubbles that provide a continuous source of treatment. Once injected, the nanobubbles distribute throughout the water column and the waterbody effectively delivering oxygen and a mild, oxidative impact even at the sediment layer. Nanobubbles are a sustainable option for increasing dissolved oxygen concentrations, improving water clarity, and overall waterbody health even in shallow or hard to treatment water bodies.

The Clear is available in 50 and 150 GPM (11 or 34 m³/hr) flow rates that use integrated compressors to supply atmospheric air.

The Clear comes standard with remote equipment monitoring capability that enables each system to be monitored by both the user and Moleaer's global team of field service technicians to ensure optimum performance. Furthermore, each system offers an optional dissolved oxygen monitoring solution that can be tracked in real time, remotely. Additional water quality monitoring solutions are also available.

Features & Benefits:

- Highest Oxygen Transfer Efficiency
- Global Remote Monitoring Capability
- Quiet, <65 dB
- 120 nm-sized Bubbles
- >1 Billion Nanobubbles / mL
- Easy to Install & Maintain
- Small Footprint & Lightweight
- Shore Mounted

Options:

- Remote Water Quality Monitoring

Lake Restore | sales@lakerestore.com | lakerestore.com | 800.450.6295

The information and data contained herein are deemed to be accurate and reliable and are offered in good faith, but without guarantee of performance. Moleaer assumes no liability for results obtained or damages incurred through the application of the information contained herein. Customer is responsible for determining whether the products and information presented herein are appropriate for the customer's use and for ensuring that customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Specifications subject to change without notice.

Copyright © 2021 Moleaer. All trademarks stated herein are the property of their respective company. All rights reserved. This document is confidential and contains proprietary information of Moleaer Inc. Neither this document nor any of the information contained herein may be reproduced, redistributed or disclosed under any circumstances without the express written permission of Moleaer Inc.

Rev. 030323

CLEAR US Series

MODELS	Clear 50	Clear 50 (230V)	Clear 150
LIQUID FLOW CAPACITY (WATER)			
Flow Rate, GPM	50	50	150
Maximum Liquid Pressure, PSIG	22		
OPERATING PARAMETERS			
Temperature Tolerance, °F	40 - 140		
Solids, inches	< 3/8		
GAS FEED			
Maximum Gas Pressure, PSIG	120		
Indicated Gas Flow Range, CFH	0 - 20		
ELECTRICAL POWER			
Voltage	115	230	230
Phase	1		
Hz	60		
Pump Motor Power (HP)	0.750	0.750	3
Total Compressor Power (HP)	0.125	0.125	0.125
Max Amp Draw	11.2	5.6	15.0
PUMP			
Pump Type	TEFC		
Wetted Parts Materials	Polypropylene/316 SS/Buna		
Motor Starter Switch	Start Button (Latching)		
UNIT CONNECTIONS			
Customer Pipe Connection	2	2	3
Unit Inlet (Slip and Groove), inches	2	2	3
Unit Discharge (Slip and Groove), inches	2	2	3
DIMENSIONS AND WEIGHT			
Height, inches	32		
Width, inches	27.5		
Length, inches	39		
Weight, lb	250	250	250
OZONE (OPTIONAL FEATURE OFFERED ONLY ON THE 150 GPM ENRICHED OPTION ONLY)			
Additional Amp Draw	NA	NA	NA
OPTIONAL FEATURES			
Remote Monitoring	Global GPS and 4G/3G service		
Dissolved Oxygen Sensor	Optical, 0 - 40 ppm (+/- 1.5 ppm), 30 Second Response Time		
OPTIONAL UPGRADE FEATURES			
Remote Monitoring	Equipment performance sensors included standard, option to upgrade to access real time data and receive notifications		
Dissolved Oxygen	Option to include Dissolved Oxygen (DO) sensor in unit and monitor data 24/7		
External Water Monitoring	Option to include additional water quality sensor to monitor Temperature, Conductivity, pH, ORP, DO, Chlorophyll-A		

Remote Monitoring: All systems are remote-monitoring ready. Subscriptions and fees apply to activate. Remote monitoring includes on-board GPS/3G sim card with worldwide connectivity.

Notes: EPA Establishment Number 94231-CA-1 Intake screen is necessary to prevent clogging.



Lake Restore | sales@lakerestore.com | lakerestore.com | 800.450.6295

The information and data contained herein are deemed to be accurate and reliable and are offered in good faith, but without guarantee of performance. Moleaer assumes no liability for results obtained or damages incurred through the application of the information contained herein. Customer is responsible for determining whether the products and information presented herein are appropriate for the customer's use and for ensuring that customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Specifications subject to change without notice.

Copyright © 2021 Moleaer. All trademarks stated herein are the property of their respective company. All rights reserved. This document is confidential and contains proprietary information of Moleaer Inc. Neither this document nor any of the information contained herein may be reproduced, redistributed or disclosed under any circumstances without the express written permission of Moleaer Inc.

Rev. 030323